



TECHNICAL DATA SHEET

Vinyl Letter Remover Delete

FOR REMOVING	ADVANTAGES
Vinyl logos, vinyl letters, and adhesive residue from clothing and other fabrics	• Methylene Chloride Free • Industrial strength • Fast Removing

GENERAL DESCRIPTION

Caseway Delete is specially formulated for removing vinyl letter, vinyl logos, and residue adhesive from clothing and other fabrics. The industrial strength solvent quickly loosens the adhesive holding the vinyl and fabric together allowing easy removal. Delete is not intended for removing vinyl logos, letters, and decals from surfaces other than fabric. It will damage coated and painted surfaces.

DIRECTIONS FOR USE

Preparation: Use proper safety equipment when handling (eyes, face, skin, hand, and respiratory). Ensure all safety precautions are read and fully understood.

*It is the responsibility of the user to test the material compatibility and method used to apply this product before actual application.

1. Moisten the inside of the garment behind the vinyl to be removed. Use a clean non colored cloth for big areas. Use a solvent dispenser or cotton swab for smaller areas. Apply to one letter/decals at a time. Large logos or numbers can be removed a portion at a time.
2. Allow at least 20 seconds for the solvent to loosen the adhesive from the fibers of the garment. The solvent evaporates quickly so you may have to re-moisten the area.
3. Slowly pull off the letter or logo.
4. If any adhesive residue remains on the garment, remove it by using the solvent the same way you would use a spot remover. Use a clean non-colored cloth to gently wipe the left adhesive residue.

Suggestions: Test the solvent on garment for fading or damage to synthetic fibers. If spotting occurs, feather edges with solvent. Keep container tightly sealed when not in use to prevent evaporation. Turn cleaning cloth frequently. Allow garment to dry and wash after solvent application.

AVAILABILITY

Available in pint (16 fl oz), quart (32 fl oz), gallon (128 fl oz), and 55 gallon drum.

STORAGE

Delete will evaporate over time. Tightly cap and seal the container as best as possible. Store in the original containers in a cool, dark area away from hot surfaces, heat, sparks, flames and other sources of ignition. Store locked up in an area not accessible to children.

SAFETY

This product is considered a hazardous material. Do not handle until all safety precautions have been read and understood. Read the product label & safety data sheet (SDS) for information on proper handling, health risks, firefighting methods, spill procedures, emergency contact information, precautionary information, disposal information & more. Safety data sheets are available at www.casewayproducts.com or by emailing support@casewayproducts.com.

NOTICE: Wear protective gloves, protective clothing, eye protection, face protection. This product should never be used in a poorly ventilated (confined) area and without a suitable respiratory mask. This product is intended for use by experienced individuals only.

* The information, suggestions, technical data, and advice provided on this sheet are based on test results, knowledge, and experience believed to be accurate and reliable. However, all information, suggestions, technical data, and advice are not to be considered a warranty and Caseway Industrial Products, Inc. assumes no liability for any direct, indirect punitive, incidental, special consequential damages, to property or life.